



# RECHARGEABLE SEALED LEAD ACID BATTERY

Revision 3.6



## WP1236W

### Specifications

**Nominal Voltage (V)** 12V

#### Nominal Capacity

20hour rate ( 0.425A to 10.50V )	8.5Ah
10hour rate ( 0.85A to 10.50V )	8.08Ah
5hour rate ( 1.445A to 10.20V )	7.23Ah
1C ( 8.5A to 9.60V )	5.95Ah
3C ( 25.5A to 9.60V )	4.25Ah

**Weight** Approx. 2.9kg(6.38Lbs.)

**Internal Resistance (at 1KHz)** 11 mΩ

**Maximum Discharge Current for 30 seconds :** 170A

**Maximum Discharge Current for 5 seconds :** 340A

#### Operating Temperature Range

Charge	0°C (32°F) to 40°C (104°F)
Discharge	-15°C (5°F) to 50°C (122°F)
Storage	-15°C (5°F) to 40°C (104°F)

#### Charge Retention (shelf life) at 20°C (68°F)

1 month	92%
3 month	90%
6 month	80%

#### Charging Methods at 20°C(68°F)

##### Cycle use:

Charging Voltage 14.4 to 15.0V  
Maximum Charging Current : 2.55A

##### Standby use :

Float Charging Voltage 13.50 to 13.80V

#### Life expectancy :

##### Cycle Use :

100% depth of discharge 225 cycles  
80% depth of discharge 250 cycles  
50% depth of discharge 750 cycles

**Standby Use :** 3~5years

**Case Material** ABS

(Option : 94-HB & 94V-0 flame retardant case)

**Terminal** F2

### Dimensions

